



Manufacturers



ALLIED
MOULDED
PRODUCTS, Inc.

NEMA 4X Non-Metallic Enclosures

- Fiberglass Enclosures: 7 x 4 x 3" to 72 x 49 x 25" (Wall Mount & Freestanding)
- Polycarbonate Enclosures: 6" x 6" x 4" to 12" x 12" x 6" (Wall Mount)
- Accessories: back panels, ventilation kits, and pole mount kits
- Custom Mods: Holes, cutouts, EMI/RFI shielding, silk screening & molded-in color
- NEMA Type: 1, 2, 3, 3R, 4, 4X, 12, and 13. UL & CSA Listed



AC Power Supplies, Frequency Converters, & VPX Power Supplies

- AC Power Sources: 400Hz, 50Hz, 60Hz In / Out and Variable, & Extended Frequency range on certain models
- Inverters: DC and AC - 400Hz, 50Hz, 60Hz In / AC 50Hz, 60Hz Out, 120VAC Output
- Ruggedized UPS: True On-Line design, Full-time Power Conditioning, & True Voltage Regulation
- VPX Power Supplies: 12 VDC, 5 VDC, 3.3 VDC+ & -12 VDC Aux Rugged, Military, Wedgelock Cooled, & High Reliability



Test and Measurement Products

- Gages and switches for pressure, temperature, level, air velocity, flow & humidity
- Handheld instruments include manometers and thermometers
- Temperature/Process controllers
- Digital data loggers and chart recorders
- Intrinsically safe versions of many products are available



FLUKE

Thermal Imagers

- Complete range of easy-to-use thermal imagers from entry level to high precision and designed to withstand up to a 6.5 ft drop
- IR-Fusion Technology allows for infrared & visible light images to be fused together
- Ideal for electrical and mechanical systems, electrical utilities, predictive maintenance, process monitoring, R&D, and building inspections
- Image analysis and reporting software included



JW WINCO
A Ganter Company

Metric and Inch Engineered Components

- Adjustable levers, casters, control levers, handles, hand wheels, knobs, & more
- Secondary machining, custom std. parts & special kit packaging/labeling available
- Over 18,000 items in stock (Online ordering available) with 2D/3D CAD files
- Free UPS Ground shipping on orders over \$50



Laboratory and Industrial Scales & Balances

- Analytical, precision, moisture analysis, portable, electronic bench scales/ balances
- Scale capacity ranges from 62 g to 270 kg
- Readability from 0.01 mg for analytical balances to .1 g for precision balances
- Options include AutoCal (Automatic Internal Calibration and NTEP approval), RS232 or USB plug-ins, and draft shield doors



Non-Contact Infrared Temperature Sensors

- Fixed mount infrared temperature sensors and scanning systems used where contact would damage or alter the surface
- Series Temperature Ranges: Compact (0-3002 F), Marathon (480-5430 F), Thermalert (0-3630 F)
- Products are used in industrial processes to provide continuous and accurate temperature monitoring